

```

[ 0.000000] Initializing cgroup subsys cpuset
[ 0.000000] Initializing cgroup subsys cpu
[ 0.000000] Linux version 2.6.34-12-default (geeko@buildhost) (gcc version 4.5.0 20100604 [gcc-4_5-branch
revision 160292] (SUSE Linux) ) #1 SMP 2010-06-29 02:39:08 +0200
[ 0.000000] BIOS-provided physical RAM map:
[ 0.000000] BIOS-e820: 0000000000000000 - 000000000009e000 (usable)
[ 0.000000] BIOS-e820: 000000000009e000 - 00000000000a0000 (reserved)
[ 0.000000] BIOS-e820: 00000000000ca000 - 00000000000cc000 (reserved)
[ 0.000000] BIOS-e820: 00000000000e0000 - 00000000000100000 (reserved)
[ 0.000000] BIOS-e820: 00000000000100000 - 000000000bfff0000 (usable)
[ 0.000000] BIOS-e820: 00000000bfff0000 - 00000000bffff000 (ACPI data)
[ 0.000000] BIOS-e820: 00000000bffff000 - 00000000bff00000 (ACPI NVS)
[ 0.000000] BIOS-e820: 00000000bff00000 - 00000000c0000000 (usable)
[ 0.000000] BIOS-e820: 00000000fec00000 - 00000000fec10000 (reserved)
[ 0.000000] BIOS-e820: 00000000fee00000 - 00000000fee01000 (reserved)
[ 0.000000] BIOS-e820: 00000000ffc00000 - 00000000100000000 (reserved)
[ 0.000000] Notice: NX (Execute Disable) protection missing in CPU or disabled in BIOS!
[ 0.000000] DMI present.
[ 0.000000] Phoenix BIOS detected: BIOS may corrupt low RAM, working around it.
[ 0.000000] e820 update range: 0000000000000000 - 0000000000010000 (usable) ==> (reserved)
[ 0.000000] e820 update range: 0000000000000000 - 0000000000001000 (usable) ==> (reserved)
[ 0.000000] e820 remove range: 00000000000a0000 - 00000000000100000 (usable)
[ 0.000000] last_pfn = 0xc0000 max_arch_pfn = 0x100000
[ 0.000000] MTRR default type: uncachable
[ 0.000000] MTRR fixed ranges enabled:
[ 0.000000] 00000-9FFFF write-back
[ 0.000000] A0000-BFFFF uncachable
[ 0.000000] C0000-C7FFF write-protect
[ 0.000000] C8000-DFFFF uncachable
[ 0.000000] E0000-FFFFFF write-protect
[ 0.000000] MTRR variable ranges enabled:
[ 0.000000] 0 base 000000000 mask F80000000 write-back
[ 0.000000] 1 base 080000000 mask FC0000000 write-back
[ 0.000000] 2 disabled
[ 0.000000] 3 disabled
[ 0.000000] 4 disabled
[ 0.000000] 5 disabled
[ 0.000000] 6 disabled
[ 0.000000] 7 disabled
[ 0.000000] PAT not supported by CPU.
[ 0.000000] Scanning 0 areas for low memory corruption
[ 0.000000] modified physical RAM map:
[ 0.000000] modified: 0000000000000000 - 0000000000010000 (reserved)
[ 0.000000] modified: 0000000000010000 - 000000000009e000 (usable)
[ 0.000000] modified: 000000000009e000 - 00000000000a0000 (reserved)
[ 0.000000] modified: 00000000000ca000 - 00000000000cc000 (reserved)
[ 0.000000] modified: 00000000000e0000 - 00000000000100000 (reserved)
[ 0.000000] modified: 00000000000100000 - 00000000bfff0000 (usable)
[ 0.000000] modified: 00000000bfff0000 - 00000000bffff000 (ACPI data)
[ 0.000000] modified: 00000000bffff000 - 00000000bff00000 (ACPI NVS)
[ 0.000000] modified: 00000000bff00000 - 00000000c0000000 (usable)
[ 0.000000] modified: 00000000fec00000 - 00000000fec10000 (reserved)
[ 0.000000] modified: 00000000fee00000 - 00000000fee01000 (reserved)
[ 0.000000] modified: 00000000ffc00000 - 00000000100000000 (reserved)
[ 0.000000] initial memory mapped : 0 - 00c00000
[ 0.000000] found SMP MP-table at [c00f6920] f6920
[ 0.000000] init_memory_mapping: 0000000000000000-00000000377fe000
[ 0.000000] 0000000000 - 0000400000 page 4k
[ 0.000000] 0000400000 - 0037400000 page 2M
[ 0.000000] 0037400000 - 00377fe000 page 4k
[ 0.000000] kernel direct mapping tables up to 377fe000 @ 15000-1a000
[ 0.000000] RAMDISK: 7edd7000 - 80000000
[ 0.000000] Allocated new RAMDISK: 009f6000 - 01c1e965

```

```

[ 0.000000] Move RAMDISK from 000000007edd7000 - 000000007fff964 to 009f6000 - 01c1e964
[ 0.000000] ACPI: RSDP 000f68b0 00014 (v00 PTLTD )
[ 0.000000] ACPI: RSDT bfefbf65 00034 (v01 PTLTD  RSDT  06040001 LTP 00000000)
[ 0.000000] ACPI: FACP bfefbf99 00074 (v01 FSC  D1306  06040001  000F4240)
[ 0.000000] ACPI: DSDT bfefc00d 02F11 (v01 FSC  D1306  06040001 MSFT 0100000C)
[ 0.000000] ACPI: FACS bfefff0 00040
[ 0.000000] ACPI: SPCR bfefef1e 00050 (v01 PTLTD  $UCRTBL$ 06040001 PTL 00000001)
[ 0.000000] ACPI: APIC bfefef6e 0006A (v01 PTLTD  ? APIC  06040001 LTP 00000000)
[ 0.000000] ACPI: BOOT bfefef8 00028 (v01 PTLTD  $SBFTBL$ 06040001 LTP 00000001)
[ 0.000000] ACPI: Local APIC address 0xfe00000
[ 0.000000] 2184MB HIGHMEM available.
[ 0.000000] 887MB LOWMEM available.
[ 0.000000] mapped low ram: 0 - 377fe000
[ 0.000000] low ram: 0 - 377fe000
[ 0.000000] Zone PFN ranges:
[ 0.000000] DMA 0x00000010 -> 0x00001000
[ 0.000000] Normal 0x00001000 -> 0x000377fe
[ 0.000000] HighMem 0x000377fe -> 0x000c0000
[ 0.000000] Movable zone start PFN for each node
[ 0.000000] early_node_map[3] active PFN ranges
[ 0.000000] 0: 0x00000010 -> 0x0000009e
[ 0.000000] 0: 0x00000100 -> 0x000bfef0
[ 0.000000] 0: 0x000bff00 -> 0x000c0000
[ 0.000000] On node 0 totalpages: 786302
[ 0.000000] free_area_init_node: node 0, pgdat c0882580, node_mem_map c1c20200
[ 0.000000] DMA zone: 32 pages used for memmap
[ 0.000000] DMA zone: 0 pages reserved
[ 0.000000] DMA zone: 3950 pages, LIFO batch:0
[ 0.000000] Normal zone: 1744 pages used for memmap
[ 0.000000] Normal zone: 221486 pages, LIFO batch:31
[ 0.000000] HighMem zone: 4369 pages used for memmap
[ 0.000000] HighMem zone: 554721 pages, LIFO batch:31
[ 0.000000] Using APIC driver default
[ 0.000000] ACPI: PM-Timer IO Port: 0xf008
[ 0.000000] ACPI: Local APIC address 0xfe00000
[ 0.000000] ACPI: LAPIC (acpi_id[0x00] lapic_id[0x03] enabled)
[ 0.000000] ACPI: LAPIC (acpi_id[0x01] lapic_id[0x00] enabled)
[ 0.000000] ACPI: LAPIC_NMI (acpi_id[0x00] high edge lint[0x1])
[ 0.000000] ACPI: LAPIC_NMI (acpi_id[0x01] high edge lint[0x1])
[ 0.000000] ACPI: IOAPIC (id[0x01] address[0xfec00000] gsi_base[0])
[ 0.000000] IOAPIC[0]: apic_id 1, version 17, address 0xfec00000, GSI 0-15
[ 0.000000] ACPI: IOAPIC (id[0x02] address[0xfec01000] gsi_base[16])
[ 0.000000] IOAPIC[1]: apic_id 2, version 17, address 0xfec01000, GSI 16-31
[ 0.000000] ACPI: INT_SRC_OVR (bus 0 bus_irq 9 global_irq 9 low level)
[ 0.000000] ACPI: IRQ9 used by override.
[ 0.000000] Using ACPI (MADT) for SMP configuration information
[ 0.000000] SMP: Allowing 2 CPUs, 0 hotplug CPUs
[ 0.000000] nr_irqs_gsi: 32
[ 0.000000] early_res array is doubled to 64 at [16000 - 167ff]
[ 0.000000] PM: Registered nosave memory: 000000000009e000 - 00000000000a0000
[ 0.000000] PM: Registered nosave memory: 00000000000a0000 - 00000000000ca000
[ 0.000000] PM: Registered nosave memory: 00000000000ca000 - 00000000000cc000
[ 0.000000] PM: Registered nosave memory: 00000000000cc000 - 00000000000e0000
[ 0.000000] PM: Registered nosave memory: 00000000000e0000 - 0000000000100000
[ 0.000000] Allocating PCI resources starting at c0000000 (gap: c0000000:3ec00000)
[ 0.000000] Booting paravirtualized kernel on bare hardware
[ 0.000000] setup_percpu: NR_CPUS:32 nr_cpumask_bits:32 nr_cpu_ids:2 nr_node_ids:1
[ 0.000000] PERCPU: Embedded 14 pages/cpu @c3800000 s34260 r0 d23084 u2097152
[ 0.000000] pcpu-alloc: s34260 r0 d23084 u2097152 alloc=1*4194304
[ 0.000000] pcpu-alloc: [0] 0 1
[ 0.000000] Built 1 zonelists in Zone order, mobility grouping on. Total pages: 780157
[ 0.000000] Kernel command line: initrd=initrd,08000600.spl ramdisk_size=512000 ramdisk_blocksize=4096
splash=silent quiet preloadlog=/dev/null vga=0x314 lang=de_DE toram

```

```

[ 0.000000] bootplash: silent mode.
[ 0.000000] PID hash table entries: 4096 (order: 2, 16384 bytes)
[ 0.000000] Dentry cache hash table entries: 131072 (order: 7, 524288 bytes)
[ 0.000000] Inode-cache hash table entries: 65536 (order: 6, 262144 bytes)
[ 0.000000] Enabling fast FPU save and restore... done.
[ 0.000000] Enabling unmasked SIMD FPU exception support... done.
[ 0.000000] Initializing CPU#0
[ 0.000000] Subtract (48 early reservations)
[ 0.000000] #1 [0000001000 - 0000002000] EX TRAMPOLINE
[ 0.000000] #2 [0000200000 - 00009f1b04] TEXT DATA BSS
[ 0.000000] #3 [00009f2000 - 00009f513c] BRK
[ 0.000000] #4 [00000f6930 - 0000100000] BIOS reserved
[ 0.000000] #5 [00000f6920 - 00000f6930] MP-table mpf
[ 0.000000] #6 [000009e000 - 000009e480] BIOS reserved
[ 0.000000] #7 [000009e5a4 - 00000f6920] BIOS reserved
[ 0.000000] #8 [000009e480 - 000009e5a4] MP-table mpc
[ 0.000000] #9 [0000010000 - 0000011000] TRAMPOLINE
[ 0.000000] #10 [0000011000 - 0000015000] ACPI WAKEUP
[ 0.000000] #11 [0000015000 - 0000016000] PGTABLE
[ 0.000000] #12 [00009f6000 - 0001c1f000] NEW RAMDISK
[ 0.000000] #13 [0001c1f000 - 0001c20000] BOOTMEM
[ 0.000000] #14 [0001c20000 - 0003420000] BOOTMEM
[ 0.000000] #15 [0003420000 - 0003420004] BOOTMEM
[ 0.000000] #16 [0003420040 - 0003420100] BOOTMEM
[ 0.000000] #17 [0003420100 - 0003420154] BOOTMEM
[ 0.000000] #18 [0003420180 - 0003423180] BOOTMEM
[ 0.000000] #19 [0003423180 - 0003423250] BOOTMEM
[ 0.000000] #20 [0003423280 - 000342f280] BOOTMEM
[ 0.000000] #21 [000342f280 - 000342f2ce] BOOTMEM
[ 0.000000] #22 [000342f300 - 000342f450] BOOTMEM
[ 0.000000] #23 [000342f480 - 000342f4c0] BOOTMEM
[ 0.000000] #24 [000342f4c0 - 000342f500] BOOTMEM
[ 0.000000] #25 [000342f500 - 000342f540] BOOTMEM
[ 0.000000] #26 [000342f540 - 000342f580] BOOTMEM
[ 0.000000] #27 [000342f580 - 000342f5c0] BOOTMEM
[ 0.000000] #28 [000342f5c0 - 000342f600] BOOTMEM
[ 0.000000] #29 [000342f600 - 000342f640] BOOTMEM
[ 0.000000] #30 [000342f640 - 000342f680] BOOTMEM
[ 0.000000] #31 [000342f680 - 000342f6c0] BOOTMEM
[ 0.000000] #32 [000342f6c0 - 000342f700] BOOTMEM
[ 0.000000] #33 [000342f700 - 000342f740] BOOTMEM
[ 0.000000] #34 [000342f740 - 000342f750] BOOTMEM
[ 0.000000] #35 [000342f780 - 000342f80a] BOOTMEM
[ 0.000000] #36 [000342f840 - 000342f8ca] BOOTMEM
[ 0.000000] #37 [0003800000 - 000380e000] BOOTMEM
[ 0.000000] #38 [0003a00000 - 0003a0e000] BOOTMEM
[ 0.000000] #39 [0003431900 - 0003431904] BOOTMEM
[ 0.000000] #40 [0003431940 - 0003431944] BOOTMEM
[ 0.000000] #41 [0003431980 - 0003431988] BOOTMEM
[ 0.000000] #42 [00034319c0 - 00034319c8] BOOTMEM
[ 0.000000] #43 [0003431a00 - 0003431aa8] BOOTMEM
[ 0.000000] #44 [0003431ac0 - 0003431b28] BOOTMEM
[ 0.000000] #45 [0003431b40 - 0003435b40] BOOTMEM
[ 0.000000] #46 [0003435b40 - 00034b5b40] BOOTMEM
[ 0.000000] #47 [00034b5b40 - 00034f5b40] BOOTMEM
[ 0.000000] Initializing HighMem for node 0 (000377fe:000c0000)
[ 0.000000] Memory: 3092892k/3145728k available (3848k kernel code, 52316k reserved, 2861k data, 408k init,
2236360k highmem)
[ 0.000000] virtual kernel memory layout:
[ 0.000000] fixmap : 0xffd33000 - 0xfffff000 (2864 kB)
[ 0.000000] pkmap : 0xff800000 - 0xffc00000 (4096 kB)
[ 0.000000] vmalloc : 0xf7ffe000 - 0xff7fe000 ( 120 MB)
[ 0.000000] lowmem : 0xc0000000 - 0xf77fe000 ( 887 MB)

```

```

[ 0.000000] .init : 0xc088e000 - 0xc08f4000 ( 408 kB)
[ 0.000000] .data : 0xc05c20f0 - 0xc088d8a8 (2861 kB)
[ 0.000000] .text : 0xc0200000 - 0xc05c20f0 (3848 kB)
[ 0.000000] Checking if this processor honours the WP bit even in supervisor mode...Ok.
[ 0.000000] Hierarchical RCU implementation.
[ 0.000000] NR_IRQS:2304 nr_irqs:512
[ 0.000000] Console: colour dummy device 80x25
[ 0.000000] console [tty0] enabled
[ 0.000000] Fast TSC calibration using PIT
[ 0.000000] Detected 995.285 MHz processor.
[ 0.008013] Calibrating delay loop (skipped), value calculated using timer frequency.. 1990.57 BogoMIPS
(lpj=3981140)
[ 0.008172] kdb version 4.4 by Keith Owens, Scott Lurndal. Copyright SGI, All Rights Reserved
[ 0.008347] Security Framework initialized
[ 0.008422] AppArmor: AppArmor initialized
[ 0.008472] Mount-cache hash table entries: 512
[ 0.008779] Initializing cgroup subsys ns
[ 0.008793] Initializing cgroup subsys cpuacct
[ 0.008807] Initializing cgroup subsys memory
[ 0.008829] Initializing cgroup subsys devices
[ 0.008836] Initializing cgroup subsys freezer
[ 0.008843] Initializing cgroup subsys net_cls
[ 0.008849] Initializing cgroup subsys blkio
[ 0.008938] mce: CPU supports 5 MCE banks
[ 0.008982] Performance Events: p6 PMU driver.
[ 0.008998] ... version: 0
[ 0.009003] ... bit width: 32
[ 0.009007] ... generic registers: 2
[ 0.009013] ... value mask: 00000000ffffff
[ 0.009018] ... max period: 000000007ffffff
[ 0.009022] ... fixed-purpose events: 0
[ 0.009027] ... event mask: 0000000000000003
[ 0.009041] Checking 'hlt' instruction... OK.
[ 0.024762] Unpacking initramfs...
[ 1.226475] Freeing initrd memory: 18596k freed
[ 1.272296] ACPI: Core revision 20100121
[ 1.283568] Enabling APIC mode: Flat. Using 2 I/O APICs
[ 1.284000] ..TIMER: vector=0x30 apic1=0 pin1=0 apic2=-1 pin2=-1
[ 1.284000] ..MP-BIOS bug: 8254 timer not connected to IO-APIC
[ 1.284000] ...trying to set up timer (IRQ0) through the 8259A ...
[ 1.284000] ..... (found apic 0 pin 0) ...
[ 1.327562] ..... works.
[ 1.327567] CPU0: Intel Pentium III (Coppermine) stepping 0a
[ 1.328000] Booting Node 0, Processors #1 Ok.
[ 0.012000] Initializing CPU#1
[ 1.420134] Brought up 2 CPUs
[ 1.420134] Total of 2 processors activated (3981.12 BogoMIPS).
[ 1.420773] devtmpfs: initialized
[ 1.420773] regulator: core version 0.5
[ 1.420773] regulator: dummy:
[ 1.420773] Time: 9:01:53 Date: 07/21/10
[ 1.420773] NET: Registered protocol family 16
[ 1.420773] ACPI: bus type pci registered
[ 1.421136] PCI: PCI BIOS revision 2.10 entry at 0xfd9aa, last bus=2
[ 1.421142] PCI: Using configuration type 1 for base access
[ 1.424506] bio: create slab <bio-0> at 0
[ 1.425851] ACPI: EC: Look up EC in DSDT
[ 1.433449] ACPI: Interpreter enabled
[ 1.433477] ACPI: (supports S0 S1 S4 S5)
[ 1.433543] ACPI: Using IOAPIC for interrupt routing
[ 1.444568] ACPI: No dock devices found.
[ 1.444583] PCI: Ignoring host bridge windows from ACPI; if necessary, use "pci=use_crs" and report a bug
[ 1.445466] ACPI: PCI Root Bridge [PCI0] (0000:00)

```

[1.447087] pci_root PNP0A03:00: host bridge window [io 0x0000-0x0cf7] (ignored)
[1.447096] pci_root PNP0A03:00: host bridge window [io 0x0d00-0x0fff] (ignored)
[1.447104] pci_root PNP0A03:00: host bridge window [io 0x1000-0x180f] (ignored)
[1.447112] pci_root PNP0A03:00: host bridge window [mem 0x000a0000-0x000bffff] (ignored)
[1.447120] pci_root PNP0A03:00: host bridge window [mem 0x000c8000-0x000dffff] (ignored)
[1.447128] pci_root PNP0A03:00: host bridge window [mem 0xec000000-0xedffffff] (ignored)
[1.447137] pci_root PNP0A03:00: host bridge window [mem 0xfed00000-0xfedffffff] (ignored)
[1.447145] pci_root PNP0A03:00: host bridge window [mem 0xfce01000-0xfbfffff] (ignored)
[1.447357] pci 0000:00:04.0: reg 10: [mem 0xed000000-0xedffffff]
[1.447368] pci 0000:00:04.0: reg 14: [io 0x1000-0x10ff]
[1.447379] pci 0000:00:04.0: reg 18: [mem 0xec020000-0xec020fff]
[1.447402] pci 0000:00:04.0: reg 30: [mem 0x00000000-0x0001ffff pref]
[1.447423] pci 0000:00:04.0: supports D1 D2
[1.447460] pci 0000:00:0a.0: reg 10: [mem 0xec021000-0xec021fff]
[1.447470] pci 0000:00:0a.0: reg 14: [io 0x1400-0x143f]
[1.447480] pci 0000:00:0a.0: reg 18: [mem 0xec000000-0xec01ffff]
[1.447500] pci 0000:00:0a.0: reg 30: [mem 0x00000000-0x000ffff pref]
[1.447520] pci 0000:00:0a.0: supports D1 D2
[1.447527] pci 0000:00:0a.0: PME# supported from D0 D1 D2 D3hot D3cold
[1.447535] pci 0000:00:0a.0: PME# disabled
[1.447622] pci 0000:00:0f.1: reg 20: [io 0x1800-0x180f]
[1.447662] pci 0000:00:0f.2: reg 10: [mem 0xec022000-0xec022fff]
[1.447720] pci_bus 0000:00: on NUMA node 0
[1.447733] ACPI: PCI Interrupt Routing Table [_SB_.PCI0._PRT]
[1.451949] ACPI: PCI Root Bridge [PCIA] (0000:01)
[1.453830] pci_root PNP0A03:01: host bridge window [io 0x1c00-0x1cff] (ignored)
[1.453839] pci_root PNP0A03:01: host bridge window [mem 0xee000000-0xee3ffff] (ignored)
[1.453848] pci_root PNP0A03:01: host bridge window [mem 0xf0000000-0xf3ffffff pref] (ignored)
[1.453901] pci 0000:01:09.0: reg 10: [mem 0xf0000000-0xf3ffffff pref]
[1.453941] pci 0000:01:09.0: reg 30: [mem 0x00000000-0x00007fff pref]
[1.454008] pci 0000:01:0a.0: reg 10: [io 0x1c00-0x1cff]
[1.454024] pci 0000:01:0a.0: reg 14: [mem 0xee002000-0xee0023ff 64bit]
[1.454039] pci 0000:01:0a.0: reg 1c: [mem 0xee000000-0xee001fff 64bit]
[1.454069] pci 0000:01:0a.0: supports D1 D2
[1.454104] pci_bus 0000:01: on NUMA node 0
[1.454114] ACPI: PCI Interrupt Routing Table [_SB_.PCIA._PRT]
[1.455446] ACPI: PCI Root Bridge [PCIB] (0000:02)
[1.457322] pci_root PNP0A03:02: host bridge window [io 0x2000-0x20ff] (ignored)
[1.457331] pci_root PNP0A03:02: host bridge window [mem 0xf4000000-0xf43ffff] (ignored)
[1.457340] pci_root PNP0A03:02: host bridge window [mem 0xf8000000-0xfbffffff pref] (ignored)
[1.457391] pci 0000:02:08.0: reg 10: [mem 0xf8000000-0xfbffffff pref]
[1.457431] pci 0000:02:08.0: reg 30: [mem 0x00000000-0x00007fff pref]
[1.457493] pci 0000:02:09.0: reg 10: [io 0x2000-0x20ff]
[1.457509] pci 0000:02:09.0: reg 14: [mem 0xf4000000-0xf4000fff 64bit]
[1.457532] pci 0000:02:09.0: reg 30: [mem 0x00000000-0x0001ffff pref]
[1.457584] pci_bus 0000:02: on NUMA node 0
[1.457594] ACPI: PCI Interrupt Routing Table [_SB_.PCIB._PRT]
[1.458467] ACPI: PCI Interrupt Link [LNKA] (IRQs 3 4 5 6 7 9 10 11 12 14 15) *0, disabled.
[1.458693] ACPI: PCI Interrupt Link [LNKB] (IRQs 3 4 5 6 7 9 10 11 12 14 15) *0, disabled.
[1.458917] ACPI: PCI Interrupt Link [LNKC] (IRQs 3 4 5 6 7 9 10 11 12 14 15) *0, disabled.
[1.459141] ACPI: PCI Interrupt Link [LNKD] (IRQs 3 4 5 6 7 9 10 11 12 14 15) *0, disabled.
[1.459364] ACPI: PCI Interrupt Link [LNKE] (IRQs 3 4 5 6 7 9 10 11 12 14 15) *0, disabled.
[1.459587] ACPI: PCI Interrupt Link [LNKF] (IRQs 3 4 5 6 7 9 10 11 12 14 15) *0, disabled.
[1.459860] ACPI: PCI Interrupt Link [LNKG] (IRQs 3 4 *5 6 7 9 10 11 12 14 15)
[1.460106] ACPI: PCI Interrupt Link [LNKH] (IRQs 3 4 5 6 7 9 10 11 12 14 15) *0, disabled.
[1.460384] ACPI: PCI Interrupt Link [LNKI] (IRQs 3 4 5 6 7 *9 10 11 12 14 15)
[1.460607] ACPI: PCI Interrupt Link [LNKJ] (IRQs 3 4 5 6 7 9 10 11 12 14 15) *0, disabled.
[1.460877] ACPI: PCI Interrupt Link [LNKK] (IRQs 3 4 5 6 7 9 10 *11 12 14 15)
[1.461098] ACPI: PCI Interrupt Link [LNKL] (IRQs 3 4 5 6 7 9 10 11 12 14 15) *0, disabled.
[1.461367] ACPI: PCI Interrupt Link [LNKM] (IRQs 3 4 5 6 7 *9 10 11 12 14 15)
[1.461634] ACPI: PCI Interrupt Link [LNKN] (IRQs 3 4 5 6 7 9 *10 11 12 14 15)
[1.461903] ACPI: PCI Interrupt Link [LNKO] (IRQs 3 4 5 6 7 9 10 *11 12 14 15)
[1.462125] ACPI: PCI Interrupt Link [LNKP] (IRQs 3 4 5 6 7 9 10 11 12 14 15) *0, disabled.

[1.462502] vgaarb: device added: PCI:0000:00:04.0,decodes=io+mem,owns=io+mem,locks=none
[1.462523] vgaarb: loaded
[1.462764] PCI: Using ACPI for IRQ routing
[1.462777] PCI: pci_cache_line_size set to 32 bytes
[1.462868] reserve RAM buffer: 000000000009e000 - 000000000009ffff
[1.462876] reserve RAM buffer: 00000000bfe00000 - 00000000bfffffff
[1.463108] NetLabel: Initializing
[1.463113] NetLabel: domain hash size = 128
[1.463118] NetLabel: protocols = UNLABELED CIPSOv4
[1.463150] NetLabel: unlabeled traffic allowed by default
[1.463183] Switching to clocksource tsc
[1.463923] AppArmor: AppArmor Filesystem Enabled
[1.463988] pnp: PnP ACPI init
[1.464040] ACPI: bus type pnp registered
[1.472320] pnp: PnP ACPI: found 14 devices
[1.472328] ACPI: ACPI bus type pnp unregistered
[1.472340] PnPBIOS: Disabled by ACPI PNP
[1.472374] system 00:01: [io 0x0370-0x0375] has been reserved
[1.472383] system 00:01: [io 0x0377] has been reserved
[1.472390] system 00:01: [io 0x040b] has been reserved
[1.472398] system 00:01: [io 0x04d0-0x04d1] has been reserved
[1.472406] system 00:01: [io 0x04d6] has been reserved
[1.472413] system 00:01: [io 0x0c00-0x0c01] has been reserved
[1.472421] system 00:01: [io 0x0c06-0x0c07] has been reserved
[1.472429] system 00:01: [io 0x0c14] has been reserved
[1.472436] system 00:01: [io 0x0c4a] has been reserved
[1.472444] system 00:01: [io 0x0c50-0x0c52] has been reserved
[1.472452] system 00:01: [io 0x0c6c] has been reserved
[1.472459] system 00:01: [io 0x0c6f] has been reserved
[1.472467] system 00:01: [io 0x0cd6-0x0cd7] has been reserved
[1.472475] system 00:01: [io 0xf100-0xf10f] has been reserved
[1.507794] pci 0000:00:0a.0: BAR 6: assigned [mem 0xc0000000-0xc00fffff pref]
[1.507807] pci 0000:00:04.0: BAR 6: assigned [mem 0xc0100000-0xc011ffff pref]
[1.507821] pci 0000:01:09.0: BAR 6: assigned [mem 0xc0120000-0xc0127fff pref]
[1.507833] pci 0000:02:09.0: BAR 6: assigned [mem 0xc0140000-0xc015ffff pref]
[1.507842] pci 0000:02:08.0: BAR 6: assigned [mem 0xc0128000-0xc012ffff pref]
[1.507852] pci_bus 0000:00: resource 0 [io 0x0000-0xffff]
[1.507858] pci_bus 0000:00: resource 1 [mem 0x00000000-0xffffffff]
[1.507867] pci_bus 0000:01: resource 0 [io 0x0000-0xffff]
[1.507874] pci_bus 0000:01: resource 1 [mem 0x00000000-0xffffffff]
[1.507881] pci_bus 0000:02: resource 0 [io 0x0000-0xffff]
[1.507888] pci_bus 0000:02: resource 1 [mem 0x00000000-0xffffffff]
[1.508051] NET: Registered protocol family 2
[1.508280] IP route cache hash table entries: 32768 (order: 5, 131072 bytes)
[1.509229] TCP established hash table entries: 131072 (order: 8, 1048576 bytes)
[1.513690] TCP bind hash table entries: 65536 (order: 7, 524288 bytes)
[1.516018] TCP: Hash tables configured (established 131072 bind 65536)
[1.516026] TCP reno registered
[1.516045] UDP hash table entries: 512 (order: 2, 16384 bytes)
[1.516127] UDP-Lite hash table entries: 512 (order: 2, 16384 bytes)
[1.516697] NET: Registered protocol family 1
[1.516778] pci 0000:00:04.0: Boot video device
[1.516819] pci 0000:00:0a.0: Firmware left e100 interrupts enabled; disabling
[1.516866] PCI: CLS 32 bytes, default 32
[1.517070] Simple Boot Flag at 0x69 set to 0x1
[1.517566] Scanning for low memory corruption every 60 seconds
[1.517950] audit: initializing netlink socket (disabled)
[1.517993] type=2000 audit(1279702912.516:1): initialized
[1.554938] highmem bounce pool size: 64 pages
[1.554956] HugeTLB registered 4 MB page size, pre-allocated 0 pages
[1.555464] VFS: Disk quotas dquot_6.5.2
[1.555546] Dquot-cache hash table entries: 1024 (order 0, 4096 bytes)
[1.555942] msgmni has been set to 427

```

[ 1.556331] alg: No test for stdrng (krng)
[ 1.556478] Block layer SCSI generic (bsg) driver version 0.4 loaded (major 254)
[ 1.556488] io scheduler noop registered
[ 1.556493] io scheduler deadline registered
[ 1.556546] io scheduler cfq registered (default)
[ 1.557110] pci-stub: invalid id string ""
[ 1.557736] vesafb: framebuffer at 0xed000000, mapped to 0xf8080000, using 1875k, total 8128k
[ 1.557745] vesafb: mode is 800x600x16, linelength=1600, pages=7
[ 1.557751] vesafb: protected mode interface info at c000:4c72
[ 1.557757] vesafb: pmi: set display start = c00c4cd8, set palette = c00c4d32
[ 1.557763] vesafb: pmi: ports = 1085 101f 10b4 10b8 1018 1014 10c0 10c3 10c1
[ 1.557779] vesafb: scrolling: redraw
[ 1.557788] vesafb: Truecolor: size=0:5:6:5, shift=0:11:5:0
[ 1.558601] boot splash 3.1.6-2004/03/31: looking for picture...
[ 1.558616] boot splash: silentjpeg size 127397 bytes
[ 1.586750] boot splash: ...found (800x600, 63072 bytes, v3).
[ 1.727550] Console: switching to colour frame buffer device 96x33
[ 1.866822] fb0: VESA VGA frame buffer device
[ 1.867022] isapnp: Scanning for PnP cards...
[ 2.176830] isapnp: No Plug & Play device found
[ 2.180885] Non-volatile memory driver v1.3
[ 2.180895] Linux agpgart interface v0.103
[ 2.180955] Serial: 8250/16550 driver, 8 ports, IRQ sharing disabled
[ 2.181144] serial8250: ttyS0 at I/O 0x3f8 (irq = 4) is a 16550A
[ 2.181335] serial8250: ttyS1 at I/O 0x2f8 (irq = 3) is a 16550A
[ 2.182355] 00:0a: ttyS0 at I/O 0x3f8 (irq = 4) is a 16550A
[ 2.182629] 00:0b: ttyS1 at I/O 0x2f8 (irq = 3) is a 16550A
[ 2.182976] Fixed MDIO Bus: probed
[ 2.183101] PNP: PS/2 Controller [PNP0303:KEYB,PNP0f13:PS2M] at 0x60,0x64 irq 1,12
[ 2.185845] serio: i8042 KBD port at 0x60,0x64 irq 1
[ 2.185866] serio: i8042 AUX port at 0x60,0x64 irq 12
[ 2.186119] mice: PS/2 mouse device common for all mice
[ 2.186357] cpuidle: using governor ladder
[ 2.186364] cpuidle: using governor menu
[ 2.214876] input: AT Translated Set 2 keyboard as /devices/platform/i8042/serio0/input/input0
[ 2.593068] TCP cubic registered
[ 2.593236] NET: Registered protocol family 10
[ 2.594241] lo: Disabled Privacy Extensions
[ 2.595005] Using IPI No-Shortcut mode
[ 2.595248] PM: Resume from disk failed.
[ 2.595294] registered taskstats version 1
[ 2.595634] Magic number: 2:498:20
[ 2.596064] Freeing unused kernel memory: 408k freed
[ 2.597129] Write protecting the kernel text: 3852k
[ 2.597290] Write protecting the kernel read-only data: 2600k
[ 3.017871] udev: starting version 157
[ 3.129454] SCSI subsystem initialized
[ 3.191481] usbcore: registered new interface driver usbfs
[ 3.191560] usbcore: registered new interface driver hub
[ 3.191622] psmouse serio1: ID: 10 00 14
[ 3.380437] alloc irq_desc for 29 on node -1
[ 3.380449] alloc kstat_irqs on node -1
[ 3.380476] sym53c8xx 0000:01:0a.0: PCI INT A -> GSI 29 (level, low) -> IRQ 29
[ 3.406405] parport_pc 00:09: reported by Plug and Play ACPI
[ 3.406449] parport0: PC-style at 0x378, irq 7 [PCSPP,TRISTATE,EPP]
[ 3.421703] alloc irq_desc for 26 on node -1
[ 3.421713] alloc kstat_irqs on node -1
[ 3.421736] aic7xxx 0000:02:09.0: PCI INT A -> GSI 26 (level, low) -> IRQ 26
[ 3.534166] sym0: <1010-66> rev 0x1 at pci 0000:01:0a.0 irq 29
[ 3.536824] usbcore: registered new device driver usb
[ 3.540151] libata version 3.00 loaded.
[ 3.645330] sym0: Symbios NVRAM, ID 7, Fast-80, SE, parity checking
[ 3.645342] sym0: open drain IRQ line driver, using on-chip SRAM

```

```

[ 3.645347] sym0: using LOAD/STORE-based firmware.
[ 3.645352] sym0: handling phase mismatch from SCRIPTS.
[ 3.716002] sym0: SCSI BUS has been reset.
[ 3.719511] scsi0 : sym-2.2.3
[ 3.729043] scsi2 : pata_serverworks
[ 3.729489] scsi3 : pata_serverworks
[ 3.729637] ata1: PATA max UDMA/33 cmd 0x1f0 ctl 0x3f6 bmdma 0x1800 irq 14
[ 3.729646] ata2: PATA max UDMA/33 cmd 0x170 ctl 0x376 bmdma 0x1808 irq 15
[ 3.738476] ehci_hcd: USB 2.0 'Enhanced' Host Controller (EHCI) Driver
[ 3.884227] ata1.01: NODEV after polling detection
[ 3.892345] ata1.00: ATAPI: SR243T, L02G, max UDMA/33
[ 3.908323] ata1.00: configured for UDMA/33
[ 3.911190] scsi 2:0:0:0: CD-ROM          MITSUMI CD-ROM SR243T  L02G PQ: 0 ANSI: 5
[ 4.091020] ohci_hcd: USB 1.1 'Open' Host Controller (OHCI) Driver
[ 4.091169] alloc irq_desc for 28 on node -1
[ 4.091176] alloc kstat_irqs on node -1
[ 4.091200] ohci_hcd 0000:00:0f.2: PCI INT A -> GSI 28 (level, low) -> IRQ 28
[ 4.091247] ohci_hcd 0000:00:0f.2: OHCI Host Controller
[ 4.091326] ohci_hcd 0000:00:0f.2: new USB bus registered, assigned bus number 1
[ 4.091411] ohci_hcd 0000:00:0f.2: irq 28, io mem 0xec022000
[ 4.119122] sr0: scsi3-mmc drive: 24x/24x cd/rw xa/form2 cdda tray
[ 4.119134] Uniform CD-ROM driver Revision: 3.20
[ 4.119432] sr 2:0:0:0: Attached scsi CD-ROM sr0
[ 4.135378] sr 2:0:0:0: Attached scsi generic sg0 type 5
[ 4.146111] usb usb1: New USB device found, idVendor=1d6b, idProduct=0001
[ 4.146122] usb usb1: New USB device strings: Mfr=3, Product=2, SerialNumber=1
[ 4.146129] usb usb1: Product: OHCI Host Controller
[ 4.146135] usb usb1: Manufacturer: Linux 2.6.34-12-default ohci_hcd
[ 4.146141] usb usb1: SerialNumber: 0000:00:0f.2
[ 4.146501] hub 1-0:1.0: USB hub found
[ 4.146517] hub 1-0:1.0: 4 ports detected
[ 4.485051] input: ImPS/2 Generic Wheel Mouse as /devices/platform/i8042/serio1/input/input1
[ 7.888759] scsi 0:0:4:0: Sequential-Access HP      C1537A      L111 PQ: 0 ANSI: 2
[ 7.888790] scsi target0:0:4: Beginning Domain Validation
[ 7.906056] scsi target0:0:4: FAST-10 SCSI 10.0 MB/s ST (100 ns, offset 31)
[ 7.920450] scsi target0:0:4: Domain Validation skipping write tests
[ 7.920460] scsi target0:0:4: Ending Domain Validation
[ 7.920930] scsi 0:0:4:0: Attached scsi generic sg1 type 1
[10.920956] st: Version 20081215, fixed bufsize 32768, s/g segs 256
[10.921831] st 0:0:4:0: Attached scsi tape st0
[10.921839] st 0:0:4:0: st0: try direct i/o: yes (alignment 4 B)
[10.932231] osst :I: Tape driver with OnStream support version 0.99.4
[10.932236] osst :I: $Id: osst.c,v 1.73 2005/01/01 21:13:34 wriede Exp $
[18.644049] scsi1 : Adaptec AIC7XXX EISA/VLB/PCI SCSI HBA DRIVER, Rev 7.0
[18.644053]      <Adaptec 29160 Ultra160 SCSI adapter>
[18.644057]      aic7892: Ultra160 Wide Channel A, SCSI Id=7, 32/253 SCBs
[18.644060]
[38.152316] brd: module loaded
[38.204904] BIOS EDD facility v0.16 2004-Jun-25, 6 devices found
[38.238874] device-mapper: uevent: version 1.0.3
[38.239878] device-mapper: ioctl: 4.17.0-ioclt (2010-03-05) initialised: dm-devel@redhat.com
[72.816060] ata1: lost interrupt (Status 0x51)
[72.816118] ata1.00: exception Emask 0x0 SAct 0x0 SErr 0x0 action 0x6 frozen
[72.816137] sr 2:0:0:0: [sr0] CDB: Read(10): 28 00 00 05 5c 00 00 00 02 00
[72.816180] ata1.00: cmd a0/01:00:00:00:10/00:00:00:00/a0 tag 0 dma 4096 in
[72.816184]      res 40/00:03:00:20:00:00:00:00/a0 Emask 0x4 (timeout)
[72.816207] ata1.00: status: { DRDY }
[72.816235] ata1: soft resetting link
[72.972207] ata1.01: NODEV after polling detection
[72.996315] ata1.00: configured for UDMA/33
[72.996527] ata1: EH complete
[103.804034] ata1: lost interrupt (Status 0x51)
[103.804070] ata1.00: exception Emask 0x0 SAct 0x0 SErr 0x0 action 0x6 frozen

```



```

[ 103.804087] sr 2:0:0:0: [sr0] CDB: Read(10): 28 00 00 05 5c 00 00 00 02 00
[ 103.804127] ata1.00: cmd a0/01:00:00:00:10/00:00:00:00:00/a0 tag 0 dma 4096 in
[ 103.804131]      res 40/00:03:00:20:00/00:00:00:00:00/a0 Emask 0x4 (timeout)
[ 103.804153] ata1.00: status: { DRDY }
[ 103.804177] ata1: soft resetting link
[ 103.960194] ata1.01: NODEV after polling detection
[ 103.984315] ata1.00: configured for UDMA/33
[ 103.984516] ata1: EH complete
[ 134.804039] ata1: lost interrupt (Status 0x51)
[ 134.804084] ata1.00: exception Emask 0x0 SAct 0x0 SErr 0x0 action 0x6 frozen
[ 134.804101] sr 2:0:0:0: [sr0] CDB: Read(10): 28 00 00 05 5c 00 00 00 02 00
[ 134.804143] ata1.00: cmd a0/01:00:00:00:10/00:00:00:00:00/a0 tag 0 dma 4096 in
[ 134.804146]      res 40/00:03:00:20:00/00:00:00:00:00/a0 Emask 0x4 (timeout)
[ 134.804169] ata1.00: status: { DRDY }
[ 134.804194] ata1: soft resetting link
[ 134.960199] ata1.01: NODEV after polling detection
[ 134.984314] ata1.00: configured for UDMA/33
[ 134.984518] ata1: EH complete
[ 165.804035] ata1: lost interrupt (Status 0x51)
[ 165.804071] ata1.00: limiting speed to UDMA/25:PIO4
[ 165.804085] ata1.00: exception Emask 0x0 SAct 0x0 SErr 0x0 action 0x6 frozen
[ 165.804101] sr 2:0:0:0: [sr0] CDB: Read(10): 28 00 00 05 5c 00 00 00 02 00
[ 165.804141] ata1.00: cmd a0/01:00:00:00:10/00:00:00:00:00/a0 tag 0 dma 4096 in
[ 165.804145]      res 40/00:03:00:20:00/00:00:00:00:00/a0 Emask 0x4 (timeout)
[ 165.804178] ata1.00: status: { DRDY }
[ 165.804203] ata1: soft resetting link
[ 165.960195] ata1.01: NODEV after polling detection
[ 165.984312] ata1.00: configured for UDMA/25
[ 165.984520] sr 2:0:0:0: [sr0] Result: hostbyte=DID_OK driverbyte=DRIVER_SENSE
[ 165.984541] sr 2:0:0:0: [sr0] Sense Key : Aborted Command [current] [descriptor]
[ 165.984562] Descriptor sense data with sense descriptors (in hex):
[ 165.984577]      72 0b 00 00 00 00 00 0e 09 0c 00 00 00 03 00 00
[ 165.984610]      00 20 00 00 a0 40
[ 165.984630] sr 2:0:0:0: [sr0] Add. Sense: No additional sense information
[ 165.984649] sr 2:0:0:0: [sr0] CDB: Read(10): 28 00 00 05 5c 00 00 00 02 00
[ 165.984681] end_request: I/O error, dev sr0, sector 1404928
[ 165.984699] Buffer I/O error on device sr0, logical block 175616
[ 165.984739] ata1: EH complete
[ 196.804036] ata1: lost interrupt (Status 0x51)
[ 196.804088] ata1.00: exception Emask 0x0 SAct 0x0 SErr 0x0 action 0x6 frozen
[ 196.804106] sr 2:0:0:0: [sr0] CDB: Read(10): 28 00 00 05 5c 00 00 00 02 00
[ 196.804149] ata1.00: cmd a0/01:00:00:00:10/00:00:00:00:00/a0 tag 0 dma 4096 in
[ 196.804153]      res 40/00:03:00:20:00/00:00:00:00:00/a0 Emask 0x4 (timeout)
[ 196.804178] ata1.00: status: { DRDY }
[ 196.804204] ata1: soft resetting link
[ 196.960205] ata1.01: NODEV after polling detection
[ 196.984312] ata1.00: configured for UDMA/25
[ 196.984519] ata1: EH complete
[ 227.804032] ata1: lost interrupt (Status 0x51)
[ 227.804078] ata1.00: limiting speed to PIO4
[ 227.804093] ata1.00: exception Emask 0x0 SAct 0x0 SErr 0x0 action 0x6 frozen
[ 227.804110] sr 2:0:0:0: [sr0] CDB: Read(10): 28 00 00 05 5c 00 00 00 02 00
[ 227.804152] ata1.00: cmd a0/01:00:00:00:10/00:00:00:00:00/a0 tag 0 dma 4096 in
[ 227.804156]      res 40/00:03:00:20:00/00:00:00:00:00/a0 Emask 0x4 (timeout)
[ 227.804181] ata1.00: status: { DRDY }
[ 227.804205] ata1: soft resetting link
[ 227.960208] ata1.01: NODEV after polling detection
[ 227.984312] ata1.00: configured for PIO4
[ 227.984514] ata1: EH complete
[ 229.358532] sr 2:0:0:0: [sr0] Result: hostbyte=DID_OK driverbyte=DRIVER_SENSE
[ 229.358558] sr 2:0:0:0: [sr0] Sense Key : Illegal Request [current]
[ 229.358578] Info fld=0x55c00, ILI
[ 229.358588] sr 2:0:0:0: [sr0] Add. Sense: Illegal mode for this track

```

[229.358618] sr 2:0:0:0: [sr0] CDB: Read(10): 28 00 00 05 5c 00 00 00 02 00
[229.358650] end_request: I/O error, dev sr0, sector 1404928
[229.358668] Buffer I/O error on device sr0, logical block 175616
[229.408030] sr 2:0:0:0: [sr0] Result: hostbyte=DID_OK driverbyte=DRIVER_SENSE
[229.408053] sr 2:0:0:0: [sr0] Sense Key : Illegal Request [current]
[229.408072] Info fld=0x55c00, ILI
[229.408082] sr 2:0:0:0: [sr0] Add. Sense: Illegal mode for this track
[229.408104] sr 2:0:0:0: [sr0] CDB: Read(10): 28 00 00 05 5c 00 00 00 02 00
[229.408135] end_request: I/O error, dev sr0, sector 1404928
[229.408150] Buffer I/O error on device sr0, logical block 175616
[229.456855] sr 2:0:0:0: [sr0] Result: hostbyte=DID_OK driverbyte=DRIVER_SENSE
[229.456904] sr 2:0:0:0: [sr0] Sense Key : Illegal Request [current]
[229.456926] Info fld=0x55c00, ILI
[229.456936] sr 2:0:0:0: [sr0] Add. Sense: Illegal mode for this track
[229.456967] sr 2:0:0:0: [sr0] CDB: Read(10): 28 00 00 05 5c 00 00 00 02 00
[229.457000] end_request: I/O error, dev sr0, sector 1404928
[229.457020] Buffer I/O error on device sr0, logical block 175616
[229.504910] sr 2:0:0:0: [sr0] Result: hostbyte=DID_OK driverbyte=DRIVER_SENSE
[229.504950] sr 2:0:0:0: [sr0] Sense Key : Illegal Request [current]
[229.504968] Info fld=0x55c00, ILI
[229.504979] sr 2:0:0:0: [sr0] Add. Sense: Illegal mode for this track
[229.505024] sr 2:0:0:0: [sr0] CDB: Read(10): 28 00 00 05 5c 00 00 00 02 00
[229.505056] end_request: I/O error, dev sr0, sector 1404928
[229.505072] Buffer I/O error on device sr0, logical block 175616
[229.552395] sr 2:0:0:0: [sr0] Result: hostbyte=DID_OK driverbyte=DRIVER_SENSE
[229.552435] sr 2:0:0:0: [sr0] Sense Key : Illegal Request [current]
[229.552454] Info fld=0x55c00, ILI
[229.552464] sr 2:0:0:0: [sr0] Add. Sense: Illegal mode for this track
[229.552486] sr 2:0:0:0: [sr0] CDB: Read(10): 28 00 00 05 5c 00 00 00 02 00
[229.552517] end_request: I/O error, dev sr0, sector 1404928
[229.552533] Buffer I/O error on device sr0, logical block 175616
[229.599242] sr 2:0:0:0: [sr0] Result: hostbyte=DID_OK driverbyte=DRIVER_SENSE
[229.599280] sr 2:0:0:0: [sr0] Sense Key : Illegal Request [current]
[229.599299] Info fld=0x55c00, ILI
[229.599310] sr 2:0:0:0: [sr0] Add. Sense: Illegal mode for this track
[229.599334] sr 2:0:0:0: [sr0] CDB: Read(10): 28 00 00 05 5c 00 00 00 02 00
[229.599365] end_request: I/O error, dev sr0, sector 1404928
[229.599381] Buffer I/O error on device sr0, logical block 175616
[229.721452] sr 2:0:0:0: [sr0] Result: hostbyte=DID_OK driverbyte=DRIVER_SENSE
[229.721479] sr 2:0:0:0: [sr0] Sense Key : Illegal Request [current]
[229.721498] Info fld=0x55c00, ILI
[229.721508] sr 2:0:0:0: [sr0] Add. Sense: Illegal mode for this track
[229.721533] sr 2:0:0:0: [sr0] CDB: Read(10): 28 00 00 05 5c 00 00 00 02 00
[229.721564] end_request: I/O error, dev sr0, sector 1404928
[229.721580] Buffer I/O error on device sr0, logical block 175616
[229.766338] sr 2:0:0:0: [sr0] Result: hostbyte=DID_OK driverbyte=DRIVER_SENSE
[229.766359] sr 2:0:0:0: [sr0] Sense Key : Illegal Request [current]
[229.766377] Info fld=0x55c00, ILI
[229.766387] sr 2:0:0:0: [sr0] Add. Sense: Illegal mode for this track
[229.766409] sr 2:0:0:0: [sr0] CDB: Read(10): 28 00 00 05 5c 00 00 00 02 00
[229.766440] end_request: I/O error, dev sr0, sector 1404928
[229.766455] Buffer I/O error on device sr0, logical block 175616
[229.810687] sr 2:0:0:0: [sr0] Result: hostbyte=DID_OK driverbyte=DRIVER_SENSE
[229.810725] sr 2:0:0:0: [sr0] Sense Key : Illegal Request [current]
[229.810744] Info fld=0x55c00, ILI
[229.810754] sr 2:0:0:0: [sr0] Add. Sense: Illegal mode for this track
[229.810776] sr 2:0:0:0: [sr0] CDB: Read(10): 28 00 00 05 5c 00 00 00 02 00
[229.810807] end_request: I/O error, dev sr0, sector 1404928
[229.810823] Buffer I/O error on device sr0, logical block 175616
[230.484713] ISO 9660 Extensions: Microsoft Joliet Level 3
[230.526053] ISO 9660 Extensions: RRIP_1991A
[232.207808] ISO 9660 Extensions: Microsoft Joliet Level 3
[232.244156] ISO 9660 Extensions: RRIP_1991A

```

[ 232.289773] fuse init (API version 7.13)
[ 234.953318] loop: module loaded
[ 235.070964] EXT4-fs (loop0): barriers disabled
[ 235.072313] EXT4-fs (loop0): mounted filesystem with ordered data mode
[ 244.491835] udev: starting version 157
[ 246.615736] input: Power Button as /devices/LNXSYSTM:00/LNXXSYBUS:00/PNP0C0C:00/input/input2
[ 246.616187] ACPI: Power Button [PWRB]
[ 246.616481] input: Power Button as /devices/LNXSYSTM:00/LNXPWRBN:00/input/input3
[ 246.616664] ACPI: Power Button [PWRF]
[ 247.115950] input: PC Speaker as /devices/platform/pcspkr/input/input4
[ 247.556005]   alloc irq_desc for 22 on node -1
[ 247.556017]   alloc kstat_irqs on node -1
[ 247.556133] DAC960 0000:01:09:0: PCI INT A -> GSI 22 (level, low) -> IRQ 22
[ 247.556522] DAC960: ***** DAC960 RAID Driver Version 2.5.49 of 21 Aug 2007 *****
[ 247.556638] DAC960: Copyright 1998-2001 by Leonard N. Zubkoff <lnz@dandelion.com>
[ 247.559321] DAC960#0: Configuring Mylex AcceleRAID 352 PCI RAID Controller
[ 247.559468] DAC960#0:   Firmware Version: 6.00-17, Channels: 2, Memory Size: 64MB
[ 247.559577] DAC960#0:   PCI Bus: 1, Device: 9, Function: 0, I/O Address: Unassigned
[ 247.559691] DAC960#0:   PCI Address: 0xF0000000 mapped at 0xF8596000, IRQ Channel: 22
[ 247.559800] DAC960#0:   Controller Queue Depth: 512, Maximum Blocks per Command: 2048
[ 247.559910] DAC960#0:   Driver Queue Depth: 511, Scatter/Gather Limit: 128 of 257 Segments
[ 247.573461] Floppy drive(s): fd0 is 1.44M
[ 247.601342] e100: Intel(R) PRO/100 Network Driver, 3.5.24-k2-NAPI
[ 247.601499] e100: Copyright(c) 1999-2006 Intel Corporation
[ 247.601683]   alloc irq_desc for 30 on node -1
[ 247.601691]   alloc kstat_irqs on node -1
[ 247.601715] e100 0000:00:0a:0: PCI INT A -> GSI 30 (level, low) -> IRQ 30
[ 247.626489] e100 0000:00:0a:0: PME# disabled
[ 247.628087] e100: eth0: e100_probe: addr 0xec021000, irq 30, MAC addr 00:30:05:44:83:ff
[ 247.665412] agpgart-serverworks 0000:00:00.0: can't determine aperture size
[ 247.665570] agpgart-serverworks 0000:00:00.0: agp_backend_initialize() failed
[ 247.665688] agpgart-serverworks: probe of 0000:00:00.0 failed with error -22
[ 247.665817] agpgart-serverworks 0000:00:00.1: can't determine aperture size
[ 247.665927] agpgart-serverworks 0000:00:00.1: agp_backend_initialize() failed
[ 247.666040] agpgart-serverworks: probe of 0000:00:00.1 failed with error -22
[ 247.666164] agpgart-serverworks 0000:00:00.2: ServerWorks CNB20HE is unsupported due to lack of
documentation
[ 247.666391] agpgart-serverworks 0000:00:00.3: ServerWorks CNB20HE is unsupported due to lack of
documentation
[ 247.671273] FDC 0 is a post-1991 82077
[ 247.704850] DAC960#0:   Physical Devices:
[ 247.705038] DAC960#0:   0:0 Vendor: SEAGATE   Model: ST318406LC   Revision: 9303
[ 247.705154] DAC960#0:   Wide Synchronous at 160 MB/sec
[ 247.705265] DAC960#0:   Serial Number: 3FE1768M000072387BRN
[ 247.705378] DAC960#0:   Disk Status: Online, 35430400 blocks
[ 247.705492] DAC960#0:   0:1 Vendor: SEAGATE   Model: ST318406LC   Revision: 9303
[ 247.705607] DAC960#0:   Wide Synchronous at 160 MB/sec
[ 247.705720] DAC960#0:   Serial Number: 3FE17A4C00002239FAB8
[ 247.705832] DAC960#0:   Disk Status: Online, 35430400 blocks
[ 247.705946] DAC960#0:   0:2 Vendor: SEAGATE   Model: ST318406LC   Revision: 9303
[ 247.706060] DAC960#0:   Wide Synchronous at 160 MB/sec
[ 247.706172] DAC960#0:   Serial Number: 3FE1EL5C0000724531ZB
[ 247.706284] DAC960#0:   Disk Status: Online, 35430400 blocks
[ 247.706397] DAC960#0:   0:7 Vendor: MYLEX    Model: AcceleRAID 352   Revision: 0600
[ 247.706512] DAC960#0:   Wide Synchronous at 160 MB/sec
[ 247.706623] DAC960#0:   Serial Number:
[ 247.706737] DAC960#0:   0:8 Vendor: SDR      Model: GEM318      Revision: 0
[ 247.706853] DAC960#0:   Asynchronous
[ 247.706967] DAC960#0:   1:0 Vendor: SEAGATE   Model: ST318406LC   Revision: 9303
[ 247.707086] DAC960#0:   Wide Synchronous at 160 MB/sec
[ 247.707200] DAC960#0:   Serial Number: 3FE1ELSZ000072454C4Z
[ 247.707315] DAC960#0:   Disk Status: Online, 35430400 blocks
[ 247.707432] DAC960#0:   1:1 Vendor: SEAGATE   Model: ST318406LC   Revision: 9303

```

```

[ 247.707549] DAC960#0:      Wide Synchronous at 160 MB/sec
[ 247.707663] DAC960#0:      Serial Number: 3FE173NT00002239GZBJ
[ 247.707777] DAC960#0:      Disk Status: Online, 35430400 blocks
[ 247.707894] DAC960#0: 1:2 Vendor: SEAGATE  Model: ST318406LC      Revision: 9303
[ 247.708045] DAC960#0:      Wide Synchronous at 160 MB/sec
[ 247.708161] DAC960#0:      Serial Number: 3FE179C000002239GZXN
[ 247.708275] DAC960#0:      Disk Status: Online, 35430400 blocks
[ 247.708389] DAC960#0: 1:7 Vendor: MYLEX   Model: AcceleRAID 352  Revision: 0600
[ 247.708503] DAC960#0:      Wide Synchronous at 160 MB/sec
[ 247.708613] DAC960#0:      Serial Number:
[ 247.708725] DAC960#0: 1:8 Vendor: SDR     Model: GEM318      Revision: 0
[ 247.708839] DAC960#0:      Asynchronous
[ 247.708947] DAC960#0: Logical Drives:
[ 247.709060] DAC960#0: /dev/rd/c0d0: RAID-1, Online, 35422208 blocks
[ 247.709174] DAC960#0:      Logical Device Initialized, BIOS Geometry: 255/63
[ 247.709292] DAC960#0:      Stripe Size: 64KB, Segment Size: 8KB
[ 247.709408] DAC960#0:      Read Cache Disabled, Write Cache Disabled
[ 247.709525] DAC960#0: /dev/rd/c0d1: RAID-1, Online, 35422208 blocks
[ 247.709640] DAC960#0:      Logical Device Initialized, BIOS Geometry: 255/63
[ 247.709758] DAC960#0:      Stripe Size: 64KB, Segment Size: 8KB
[ 247.709874] DAC960#0:      Read Cache Disabled, Write Cache Disabled
[ 247.709992] DAC960#0: /dev/rd/c0d2: RAID-1, Online, 35422208 blocks
[ 247.710109] DAC960#0:      Logical Device Initialized, BIOS Geometry: 255/63
[ 247.710227] DAC960#0:      Stripe Size: 64KB, Segment Size: 8KB
[ 247.710344] DAC960#0:      Read Cache Disabled, Write Cache Disabled
[ 247.711208] rd/c0d0: p1 p2 p3
[ 247.722857] rd/c0d1: p1
[ 247.730268] rd/c0d2: p1
[ 247.753243] alloc irq_desc for 24 on node -1
[ 247.753253] alloc kstat_irqs on node -1
[ 247.753278] DAC960 0000:02:08:0: PCI INT A -> GSI 24 (level, low) -> IRQ 24
[ 247.766082] rtc_cmos 00:03: RTC can wake from S4
[ 247.766543] rtc_cmos 00:03: rtc core: registered rtc_cmos as rtc0
[ 247.766723] rtc0: alarms up to one month, y3k, 114 bytes nvram
[ 247.770903] piix4_smbus 0000:00:0f:0: SMBus Host Controller at 0xf100, revision 0
[ 247.787875] DAC960#1: Configuring Mylex AcceleRAID 352 PCI RAID Controller
[ 247.788066] DAC960#1: Firmware Version: 6.00-17, Channels: 2, Memory Size: 64MB
[ 247.788189] DAC960#1: PCI Bus: 2, Device: 8, Function: 0, I/O Address: Unassigned
[ 247.788318] DAC960#1: PCI Address: 0xF8000000 mapped at 0xF8790000, IRQ Channel: 24
[ 247.788441] DAC960#1: Controller Queue Depth: 512, Maximum Blocks per Command: 2048
[ 247.788564] DAC960#1: Driver Queue Depth: 511, Scatter/Gather Limit: 128 of 257 Segments
[ 248.130353] DAC960#1: Physical Devices:
[ 248.130525] DAC960#1: 0:0 Vendor: FUJITSU  Model: MAP3735NC      Revision: 5207
[ 248.130649] DAC960#1:      Wide Synchronous at 160 MB/sec
[ 248.130768] DAC960#1:      Serial Number: UPD4P3900WS5
[ 248.130888] DAC960#1:      Disk Status: Online, 142131200 blocks
[ 248.131009] DAC960#1: 0:2 Vendor: FUJITSU  Model: MAP3367NC      Revision: 5207
[ 248.131130] DAC960#1:      Wide Synchronous at 160 MB/sec
[ 248.131248] DAC960#1:      Serial Number: UPP4P3902S64
[ 248.131365] DAC960#1:      Disk Status: Online, 71065600 blocks
[ 248.131484] DAC960#1: 0:7 Vendor: MYLEX   Model: AcceleRAID 352  Revision: 0600
[ 248.131604] DAC960#1:      Wide Synchronous at 160 MB/sec
[ 248.131722] DAC960#1:      Serial Number:
[ 248.131840] DAC960#1: 0:8 Vendor: QLogic  Model: GEM359      Revision: 1.09
[ 248.131960] DAC960#1:      Asynchronous
[ 248.132206] DAC960#1:      Serial Number: 1
[ 248.132329] DAC960#1: 1:0 Vendor: FUJITSU  Model: MAP3735NC      Revision: 5207
[ 248.132452] DAC960#1:      Wide Synchronous at 160 MB/sec
[ 248.132571] DAC960#1:      Serial Number: UPD4P39012TE
[ 248.132690] DAC960#1:      Disk Status: Online, 142131200 blocks
[ 248.132810] DAC960#1: 1:2 Vendor: FUJITSU  Model: MAP3735NC      Revision: 5207
[ 248.133067] DAC960#1:      Wide Synchronous at 160 MB/sec
[ 248.133188] DAC960#1:      Serial Number: UPD4P39013HP

```

[248.133303] DAC960#1: Disk Status: Online, 142131200 blocks
[248.133419] DAC960#1: 1:7 Vendor: MYLEX Model: AcceleRAID 352 Revision: 0600
[248.133535] DAC960#1: Wide Synchronous at 160 MB/sec
[248.133648] DAC960#1: Serial Number:
[248.133762] DAC960#1: 1:8 Vendor: QLogic Model: GEM359 Revision: 1.09
[248.133879] DAC960#1: Asynchronous
[248.133991] DAC960#1: Serial Number: 1
[248.134103] DAC960#1: Logical Drives:
[248.134219] DAC960#1: /dev/rd/c1d0: RAID-1, Online, 142131200 blocks
[248.134337] DAC960#1: Logical Device Initialized, BIOS Geometry: 255/63
[248.134457] DAC960#1: Stripe Size: 64KB, Segment Size: 8KB
[248.134575] DAC960#1: Read Cache Disabled, Write Cache Disabled
[248.134694] DAC960#1: /dev/rd/c1d1: RAID-7, Online, 142131200 blocks
[248.134810] DAC960#1: Logical Device Initialized, BIOS Geometry: 255/63
[248.134929] DAC960#1: Stripe Size: 64KB, Segment Size: 8KB
[248.135047] DAC960#1: Read Cache Disabled, Write Cache Disabled
[248.135167] DAC960#1: /dev/rd/c1d2: RAID-7, Online, 71057408 blocks
[248.135284] DAC960#1: Logical Device Initialized, BIOS Geometry: 255/63
[248.135403] DAC960#1: Stripe Size: 64KB, Segment Size: 8KB
[248.135523] DAC960#1: Read Cache Disabled, Write Cache Disabled
[248.136814] rd/c1d0: p1
[248.150171] rd/c1d1: p1
[248.163014] rd/c1d2: p1
[253.644503] type=1505 audit(1279703164.644:2): operation="profile_load" pid=2132 name=/bin/ping
[253.786353] type=1505 audit(1279703164.784:3): operation="profile_load" pid=2133 name=/sbin/klogd
[254.114871] type=1505 audit(1279703165.113:4): operation="profile_load" pid=2134 name=/sbin/syslog-ng
[254.390213] type=1505 audit(1279703165.389:5): operation="profile_load" pid=2135 name=/sbin/syslogd
[254.706682] type=1505 audit(1279703165.704:6): operation="profile_load" pid=2136 name=/usr/sbin/avahi-daemon
[254.954858] type=1505 audit(1279703165.953:7): operation="profile_load" pid=2137 name=/usr/sbin/identd
[255.227125] type=1505 audit(1279703166.224:8): operation="profile_load" pid=2138 name=/usr/sbin/mdnsd
[255.540518] type=1505 audit(1279703166.537:9): operation="profile_load" pid=2139 name=/usr/sbin/nsd
[256.000341] type=1505 audit(1279703167.000:10): operation="profile_load" pid=2140 name=/usr/sbin/ntpd
[256.243437] type=1505 audit(1279703167.241:11): operation="profile_load" pid=2141 name=/usr/sbin/traceroute
[257.712438] DAC960#0: Physical Device 1:8 Found
[257.712552] DAC960#0: Physical Device 0:8 Found
[257.712632] DAC960#0: Physical Device 0:0 Found
[257.712726] DAC960#0: Physical Device 0:1 Found
[257.712814] DAC960#0: Physical Device 0:2 Found
[257.712909] DAC960#0: Physical Device 1:0 Found
[257.712997] DAC960#0: Physical Device 1:1 Found
[257.713091] DAC960#0: Physical Device 1:2 Found
[257.713189] DAC960#0: Physical Device 0:0 Online
[257.713279] DAC960#0: Physical Device 1:0 Online
[257.713375] DAC960#0: Physical Device 0:1 Online
[257.713469] DAC960#0: Physical Device 1:1 Online
[257.713567] DAC960#0: Physical Device 0:2 Online
[257.713661] DAC960#0: Physical Device 1:2 Online
[257.713760] DAC960#0: Logical Drive 0 (/dev/rd/c0d0) Found
[257.713853] DAC960#0: Logical Drive 0 (/dev/rd/c0d0) Online
[257.713950] DAC960#0: Logical Drive 1 (/dev/rd/c0d1) Found
[257.714047] DAC960#0: Logical Drive 1 (/dev/rd/c0d1) Online
[257.714148] DAC960#0: Logical Drive 2 (/dev/rd/c0d2) Found
[257.714247] DAC960#0: Logical Drive 2 (/dev/rd/c0d2) Online
[257.738425] vboxguest: VirtualBox Guest PCI device not found.
[258.137113] DAC960#1: Physical Device 0:8 Found
[258.137942] DAC960#1: Physical Device 1:8 Found
[258.138028] DAC960#1: Physical Device 1:0 Found
[258.139679] DAC960#1: Physical Device 1:2 Found
[258.139760] DAC960#1: Physical Device 0:0 Found
[258.141436] DAC960#1: Physical Device 0:2 Found
[258.141523] DAC960#1: Physical Device 0:0 Online
[258.143179] DAC960#1: Physical Device 1:0 Online
[258.143281] DAC960#1: Physical Device 1:2 Online

[258.144929] DAC960#1: Physical Device 0:2 Online
[258.145039] DAC960#1: Logical Drive 0 (/dev/rd/c1d0) Found
[258.146730] DAC960#1: Logical Drive 0 (/dev/rd/c1d0) Online
[258.146827] DAC960#1: Logical Drive 1 (/dev/rd/c1d1) Found
[258.148488] DAC960#1: Logical Drive 1 (/dev/rd/c1d1) Online
[258.148597] DAC960#1: Logical Drive 2 (/dev/rd/c1d2) Found
[258.151100] DAC960#1: Logical Drive 2 (/dev/rd/c1d2) Online
[258.151187] DAC960#1: Enclosure 0 Fan 0 OK
[258.153517] DAC960#1: Enclosure 1 Fan 0 OK
[258.153615] DAC960#1: Enclosure 0 Power Supply 0 OK
[258.155435] DAC960#1: Enclosure 0 Temperature Sensor 0 Temperature Normal
[258.155532] DAC960#1: Enclosure 0 Fan 0 OK
[258.156844] DAC960#1: Enclosure 1 Fan 0 OK
[258.156962] DAC960#1: Enclosure 0 Power Supply 0 OK
[258.157051] DAC960#1: Enclosure 0 Temperature Sensor 0 Temperature Normal
[261.639335] powernow: This module only works with AMD K7 CPUs
[286.878631] e100 0000:00:0a:0: firmware: requesting e100/d101s_ucode.bin
[288.886264] ADDRCONF(NETDEV_UP): eth0: link is not ready
[288.889302] e100: eth0 NIC Link is Up 100 Mbps Full Duplex
[288.900337] ADDRCONF(NETDEV_CHANGE): eth0: link becomes ready
[290.275112] NET: Registered protocol family 17
[299.264369] eth0: no IPv6 routers present
[299.590291] bootplash: status on console 0 changed to on
[304.870372] RPC: Registered udp transport module.
[304.870382] RPC: Registered tcp transport module.
[304.870388] RPC: Registered tcp NFSv4.1 backchannel transport module.
[305.045851] Slow work thread pool: Starting up
[305.053270] Slow work thread pool: Ready
[305.053449] FS-Cache: Loaded
[305.209722] FS-Cache: Netfs 'nfs' registered for caching
[338.329055] end_request: I/O error, dev fd0, sector 0
[338.476033] end_request: I/O error, dev fd0, sector 0
[1581.868036] usb 1-2: new full speed USB device using ohci_hcd and address 2
[1582.084015] usb 1-2: New USB device found, idVendor=126f, idProduct=0163
[1582.084026] usb 1-2: New USB device strings: Mfr=1, Product=2, SerialNumber=3
[1582.084034] usb 1-2: Product: 128M Mobile-Disk
[1582.084039] usb 1-2: Manufacturer: FK310-
[1582.084044] usb 1-2: SerialNumber: 93748ea53ec5ab
[1583.637842] Initializing USB Mass Storage driver...
[1583.638266] scsi4 : usb-storage 1-2:1.0
[1583.638662] usbcore: registered new interface driver usb-storage
[1583.638670] USB Mass Storage support registered.
[1584.644919] scsi 4:0:0:0: Direct-Access FK310- 128M Mobile-Disk 1.00 PQ: 0 ANSI: 2
[1584.645500] sd 4:0:0:0: Attached scsi generic sg2 type 0
[1584.659988] sd 4:0:0:0: [sda] 256000 512-byte logical blocks: (131 MB/125 MiB)
[1584.666925] sd 4:0:0:0: [sda] Write Protect is off
[1584.666940] sd 4:0:0:0: [sda] Mode Sense: 00 00 00 00
[1584.666947] sd 4:0:0:0: [sda] Assuming drive cache: write through
[1584.699905] sd 4:0:0:0: [sda] Assuming drive cache: write through
[1584.699927] sda: sda1
[1584.779884] sd 4:0:0:0: [sda] Assuming drive cache: write through
[1584.779900] sd 4:0:0:0: [sda] Attached SCSI removable disk